



US008641125B2

(12) **United States Patent**
Jimenez et al.

(10) **Patent No.:** **US 8,641,125 B2**
(45) **Date of Patent:** **Feb. 4, 2014**

(54) **SENSOR INSTALLATIONS FOR MOTORIZED VEHICLE DOORS**

(75) Inventors: **Jorge Jimenez**, Downers Grove, IL (US); **Nick Scholtes**, Shorewood, IL (US); **Robert C. Signaigo**, Lemont, IL (US)

(73) Assignee: **Control Solutions LLC**, Aurora, IL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 356 days.

(21) Appl. No.: **13/049,679**

(22) Filed: **Mar. 16, 2011**

(65) **Prior Publication Data**

US 2011/0162279 A1 Jul. 7, 2011

Related U.S. Application Data

(62) Division of application No. 12/197,126, filed on Aug. 25, 2008, now Pat. No. 7,959,211.

(51) **Int. Cl.**
B60J 5/00 (2006.01)

(52) **U.S. Cl.**
USPC **296/146.4**

(58) **Field of Classification Search**
USPC 296/146.4; 248/231.81, 316.7, 74.1;
49/26

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,413,444 A * 11/1983 Chikaraishi 49/409
4,667,910 A * 5/1987 Atterby et al. 248/71

5,295,334 A	3/1994	Haraden	
5,459,962 A	10/1995	Bonne et al.	
5,489,708 A	2/1996	Bailey et al.	
5,619,774 A	4/1997	Perry	
5,793,005 A	8/1998	Kato	
5,880,421 A	3/1999	Tsuge et al.	
6,073,899 A	6/2000	Omrani	
6,081,008 A	6/2000	Ishihara et al.	
6,233,872 B1	5/2001	Glawgow et al.	
6,253,507 B1 *	7/2001	Martino	52/211
6,327,758 B1 *	12/2001	Petrakis et al.	24/546
6,337,549 B1	1/2002	Bledin	
6,339,305 B1	1/2002	Ishihara et al.	
6,389,572 B1	5/2002	Rosenau	
6,483,045 B1	11/2002	Suzuki et al.	
6,484,365 B1	11/2002	Thompson	
6,547,201 B2	4/2003	Barich et al.	
6,747,399 B1	6/2004	Ogino et al.	
7,015,666 B2	3/2006	Staus	
D546,610 S *	7/2007	Blanchard	D6/567

(Continued)

FOREIGN PATENT DOCUMENTS

JP 2004-116027 4/2004

Primary Examiner — Rexford Barnie


Assistant Examiner — Rasem Mourad

(74) *Attorney, Agent, or Firm* — McCracken & Frank LLC

(57) **ABSTRACT**

An obstruction detection system using a safety switch with a plurality of sensors is provided. The sensors include a sensing element molded in a casing and separated from an adjacent sensor by one of a plurality of connectors. A clip has a strip portion and a first attachment arm extending at an angle from the strip portion. A second attachment arm extends from the strip portion. A barb leg is disposed at an angle relative to the strip portion. The barb leg has a first leg end and a second leg end opposite the first leg end with the barb leg connected at the first leg end to the second attachment arm and the second leg end is disposed toward and spaced apart from the strip portion.

6 Claims, 8 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

7,258,315 B2 *	8/2007	Wamsley	248/231.81	D626,438 S	11/2010	Prichard et al.	
7,323,885 B2 *	1/2008	Gutendorf	324/663	8,408,622 B2 *	4/2013	Yanai et al.	296/1.08
7,513,166 B2	4/2009	Shank et al.		2002/0088662 A1	7/2002	Kleinberg	
7,518,327 B2	4/2009	Newman et al.		2003/0085679 A1	5/2003	Bledin et al.	
7,712,256 B2 *	5/2010	Kato et al.	49/26	2003/0230690 A1	12/2003	Ostrovsky et al.	
7,753,419 B2	7/2010	Kondo		2004/0094682 A1 *	5/2004	Waterman	248/309.1
7,819,365 B2 *	10/2010	Elsner	248/74.3	2005/0012484 A1	1/2005	Gifford et al.	
				2005/0179415 A1	8/2005	Nakano et al.	
				2006/0087418 A1	4/2006	Takeuchi	
				2008/0303685 A1	12/2008	Nakano et al.	

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 8




FIG. 9




FIG. 10




FIG. 11

1

SENSOR INSTALLATIONS FOR MOTORIZED VEHICLE DOORS

CROSS-REFERENCE TO RELATED APPLICATION

This application is a divisional of U.S. patent application Ser. No. 12/197,126, filed Aug. 25, 2008 and titled SENSOR INSTALLATIONS FOR MOTORIZED VEHICLE DOORS, which is incorporated by reference in this application in its entirety.

FIELD OF THE INVENTION

This invention relates to sensors and sensor installation devices. More particularly, the invention is related to a sensor and a clip that is used to install the sensor, such as around a perimeter of a motorized door to detect obstructions between a closing door and a door frame.

BACKGROUND

To further protect military personnel during combat, military vehicles can be provided with layers of armor. In some vehicles, the armor may be provided on the vehicle in the factory during manufacture of the vehicle. However, it has become increasingly common for armor to be applied to existing vehicles in the field.

The military started adding armor to various vehicles such as, for example, its High Mobility Multipurpose Wheeled Vehicle, or "HMMWV" or "Humvee," well before Operation Iraqi Freedom, but attacks from small arms, rocket-propelled grenades and "improvised explosive devices," or IEDs in military parlance, prompted the military to increase protection for vehicles already in the field. The "up-armored" HMMWV can weigh thousands of pounds more than the standard HMMWV and includes several hundred pound steel-plated doors. Such heavy armored doors make opening and closing the doors increasingly difficult for personnel.

In co-pending and commonly assigned U.S. patent application Ser. Nos. 12/194,895 and 12/194,966, there is provided a mechanism for assisting in moving heavy armored doors on military vehicles. Such a mechanism can be retrofitted to existing vehicles that are up-armored in the field. To promote safety with such motorized door assist systems, sensors can be desirably applied to ensure the door stops when an object or body part is in the way of door closing. There is a need for such a sensor system that can be applied to vehicle doors, and retrofitted to vehicles that are up-armored in the field.

In particular, as many military vehicles were not designed in order to have sensor parts attached thereto, there is a need for a sensor system that can be retrofitted to parts of vehicle doors that have manufacturing variability, e.g., slightly misaligned parts from one door to the next in the same type of vehicle. Misalignments in welded door parts, albeit small and inconsequential to the structure and strength of the door, can present problems for parts designed to be attached to these welded parts as the variations can cause fit problems.

SUMMARY

An obstruction detection system that can be used and retrofitted to automated doors or other moving parts is provided. Methods for attaching sensors, cables, or other items to doors, such as retrofitted armored vehicle doors are also provided.

A method of retrofitting a door of a vehicle with an obstruction detection system is also provided. The method includes

2

providing a safety switch having a plurality of sensors and providing a clip for mounting a portion of the safety switch to the door. The clip is mounted to the door and the safety switch is attached to the clip, before or after the clip is mounted to the door.

An obstruction detection system using a safety switch with a plurality of sensors is provided. The sensors include a sensing element molded in a casing and separated from an adjacent sensor by one of a plurality of connectors. A clip has a strip portion and a first attachment arm extending at an angle from the strip portion. A second attachment arm extends from the strip portion. A barb leg is disposed at an angle relative to the strip portion. The barb leg has a first leg end and a second leg end opposite the first leg end with the barb leg connected at the first leg end to the second attachment arm and the second leg end is disposed toward and spaced apart from the strip portion.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates an exemplary vehicle door including a motorized door assist system.

FIGS. 2 and 3 illustrate a safety switch according to one example embodiment.

FIGS. 4A-C illustrate a clip according to one example embodiment.

FIGS. 5A-C illustrate a clip according to another example embodiment.

FIGS. 6A-C illustrate a clip according to another example embodiment.

FIGS. 7A-C illustrate a clip according to yet another example embodiment.

FIG. 8 illustrates a clip and mounting bracket combination according to one example embodiment.

FIGS. 9-11 illustrate an example of a sensor switch applied to a vehicle door by clips.

DETAILED DESCRIPTION

A clip for securing one object relative to another, such as securing an object to a vehicle door or frame is provided. In one embodiment, the clip is used to retrofit a vehicle door with a strip of safety sensors, and, more particularly, may retrofit vehicle doors that are not originally intended to be retrofitted in this way. Co-pending patent application Ser. Nos. 12/194,895 and 12/194,966 provide an apparatus for assisting in moving heavy armored doors on military vehicles. Such an apparatus can be retrofitted to existing vehicles that are up-armored in the field. To promote safety with such motorized door assist systems, sensors can be applied to ensure the door stops when an object or body part is in the way of door closing. FIG. 1 is an example armored vehicle door as described in the co-pending patent application Ser. Nos. 12/194,895 and 12/194,966, entitled "Door Assist System and Method For Retrofit Installation of Apparatus" and "Door Assist System Controller and Method" respectively, herein incorporated by reference.

The door 20 of FIG. 1 includes a safety sensor, referred to herein as safety switch 22. The safety switch 22 activates should the automated door 20 be closing and any part of the switch 22 is depressed. When depressed the switch 22 will cause the moving door 20 to immediately cease and, optionally, open a small amount. This safety mechanism is intended to prevent door closures while obstructions remain between the door and the door frame. The safety switch 22, which is connected to a control box 21, can include one or more sensors 24 strategically placed around at least portions of the

3

outside perimeter of the door. In one embodiment, the safety switch 22 includes a multi-segmented, large surface area, single pole switch, as generally illustrated in FIGS. 2 and 3, that is located around at least portions of the inside perimeter of the door.

The safety switch 22 of FIG. 2 includes a plurality of sensors 24 connected by electrical connectors, e.g., wires or cables 26. Each sensor 24 includes a touch-sensitive sensing element 28 (e.g., a stainless steel electrode) molded in a semi-circular polymer casing 30. The cables 26 can also be enclosed by the polymer casing 30, which can be formed of various deformable polymer materials, such as rubber or polyurethane. The length and spacing of the individual sensors 24, and thus the length of the intermediate cables 26, are dependent on the need of the installation. In one example, the safety switch may be a modified version of the SENSISWITCH available from Recora (Batavia, Ill.), but the safety switch is not intended to be limited to any particular size, shape, sensor type, or materials of formation.

In one embodiment, as shown in FIG. 3, the semi-circular sensor 24 can be secured to a surface by a mounting bracket 32. The mounting bracket 32 can be a metal or plastic mounting bracket that is in turn attached to the vehicle door, such as using the clips discussed below. The sensor 24 can be held in the mounting bracket 32 by any suitable means, such as an adhesive, double sided adhesive tape, or by being secured by angled bracket arms 34. The sensor 24 can, for example, clip into or slide in from an end of the bracket 32, and be held by the angled bracket arms 34. The sensors 24, for example, may include molded-in threaded nuts or other fasteners for use in attaching to the clip or bracket.

As discussed above, the Humvee vehicle doors are commonly retrofitted with heavy armor in the field. Thus the motorized door system and safety sensors discussed above are also desirably retrofitted to existing doors. As it is generally undesirable to drill into the armored doors, the present invention provides clips for attaching the safety strips to the vehicle doors. FIGS. 4A-C illustrate particular embodiments of clips useful to apply the safety strip. The clips may be designed to attach to "L" or "I"-shaped flanges of any vehicle, thereby allowing the sensor system to be retrofitted to any type of vehicle door without the need for drilling or a special tool. FIGS. 9-11 illustrate embodiments of the clips attaching a safety switch sensor to a vehicle door.

FIGS. 4A-C illustrate a clip 40 according to one embodiment. The clip 40 included a strip portion 42 to which the safety switch or a mounting bracket can be attached. As shown in FIGS. 4A-B, the strip portion 42 can include one or more countersunk mounting apertures 44. Fasteners can extend through the mounting apertures 44 for connecting a mounting bracket to the strip portion 42.

A first attachment arm 46 extends at an angle, more particularly substantially perpendicular, from the generally planar strip portion 42. In the example shown in FIGS. 4A-C, an attachment tab 48 extends at an angle from an end 49 of the first attachment arm 46 that is opposite a second end 50 of the first attachment arm 46 that is connected to the strip portion 42. As shown in FIG. 4C, the first attachment arm 46 and the attachment tab 48 secure over one end of an "L"-shaped portion, e.g., flange 45, of a vehicle door. The attachment tab 48 is desirably curved to facilitate attachment to the flange 45. The properties of the clip material and the dimensioning of the first attachment arm 46 and tab 48 allow for a gripping force on the thickness of the flange 45, and the curved tab 48 allows the clip 40 to be easily installed over the top of the flange.

4

A second attachment arm 54 extends at an angle, more particularly substantially perpendicular in FIGS. 4A-C, from an opposite end of the strip portion 42 from the first attachment arm 46. Thus, the second attachment arm 54 is substantially parallel to the first attachment arm 46. As shown in FIG. 4C, the second attachment arm 54 secures around an opposite end of the flange 45 from the first attachment arm 46. The second attachment arm 54 can optionally include an angled end portion 56 for facilitating attachment to the flange 45.

The clip 40 includes two barb legs 60 disposed at an angle relative the strip portion 42. The barb legs 60 each include a first leg end 62 and a second leg end 64 opposite the first leg end 62. Each of the barb legs 60 is connected at the first leg end 62 to the second attachment arm 54, and the second leg end 64 is disposed toward and spaced apart from the strip portion 42. The second leg end 64 is desirably bent toward the direction of the first attachment arm 46 and the flange 45, and, as shown in FIG. 4C, assists in securely holding the clip 40 on the flange 45. The clip 40 optionally includes a recess space 66 disposed adjacent to a side end 68 of each of the barb legs 60. The recess spaces 66, which separate the barb leg side ends 68 from the second attachment arm 54, can be used for facilitating removal of the clip 40 with a tool such as a screwdriver. Furthermore, the placement of the barb legs 60 toward the outer side edges of the clip 40 also facilitates removal of the clip 40.

As shown in FIG. 4C, the flange 45 is formed of a horizontal portion and a vertical portion. In the example of the clip 40 shown, the barb legs 60 are designed to contact the bottom surface of the vertical portion of the flange. This can be particularly beneficial when the flange 45 is formed from the vertical portion being welded to the horizontal portion. It is common that the welded connection of the horizontal and vertical portions is not flush. By having the barb legs 60 contact the vertical portion, the clip 40 is assured a secured fit even when the flange components are misaligned. Also, the vertical portion of the flange 45 is often composed of several sections around the door horizontal flange, and having multiple clips attached to a single bracket which may span more than one vertical portion, any misalignment in the vertical portions can be better accommodated. In this manner, the clips and safety sensor may allow for retrofitting vehicle doors that were not intended to be retrofitted in this way.

As will be appreciated by those skilled in the art following the teachings herein provided, various sizes, shapes, and configurations are available for the clip depending on need, such as depending on the configuration of the vehicle door. Further, various and alternative materials can be used to form the clip. In one example, the clips may be formed at least in part from spring steel.

FIGS. 5A-C illustrate a clip 70 according to another embodiment, which is a variation of the clip in FIGS. 4A-C. Clip 70 includes a strip portion 72, a first attachment arm 74 and a second attachment arm 76 as discussed above, and which function as discussed above. Clip 70 differs from clip 40 discussed above, by including a curved cable clamp 80 extending from an end 82 of a second attachment arm 76 that is opposite the strip portion 72. The cable clamp 80 is particularly useful for holding electrical connectors (i.e., electrical connection devices or electrical conductors), such as a cable 26 of the safety switch 22 shown in FIG. 2.

The clip 70 can be used in combination with the clip 40 to secure, for example, the safety switch 22 to a vehicle door such as shown in FIG. 1. The clip 40 can be used to secure the sensor 24 portion of the safety switch 22, and the clip 70 can be used to secure the cable 26. In the example shown in FIGS. 5A-C, the clip 70 does not include any optional countersunk

5

mounting aperture, as this clip **70** is designed for securing the cable **26**. However, clip **70** can include one or more countersunk apertures if a single, dual-purpose clip is desired.

FIGS. 6A-C illustrate a clip **90** according to yet another example embodiment. Whereas the clips **40** and **70** discussed above are designed for a bent or "L"-shaped flange, such as shown in FIG. 4C, the clip **90** is designed for a straight or "I"-shaped door lip or flange, such as shown in FIG. 6C.

Clip **90** includes a substantially planar strip portion **92** including a countersunk mounting aperture **94** for receiving a fastener therethrough. The clip **90** includes two first attachment arms **96** extending at an angle (e.g., substantially perpendicular) from the strip portion **92** at a first end **98** of the strip portion **92**. A second attachment arm **100** also extends from the first end **98** of the strip portion **92**. The second attachment arm **100** includes a curved portion **102** extending from the first end **98** of the strip portion **92**. The curved portion **102** is disposed between the two first attachment arms **96**. The two first attachment arms **96** provide for proper alignment of the sensor or cable around the flange **115** as they limits the depth to which the flange **115** penetrates into the clip **90**. Incorrect placement of the clip **90** on the flange can result in the safety switches being rendered inoperable due to incorrect placement and/or the cable being disposed in a pinch point of the door perimeter.

The clip **90** includes two barb legs **106** disposed at an end **105** of the second attachment arm **100** that is opposite the strip portion **92**. Each of the barb legs **106** is disposed at an angle relative the strip portion **92**. Each of the barb legs includes a first leg end **108** and a second leg end **110** that is opposite the first leg end **108**. Each barb leg **106** is connected at the first leg end **108** to the second attachment arm **100** and the second leg end **110** is disposed or pointed toward and spaced apart from the strip portion **92**. In the embodiment shown in FIGS. 6A-C, the second attachment arm **100** includes a curved end portion **112**, from which the barb legs are cut or stamped. A recess **114** is optionally formed between a side edge **116** of each barb leg **106** and a portion of the second attachment arm **100**.

FIGS. 7A-C illustrate a clip **120** according to another example embodiment, which is a variation of the clip in FIGS. 6A-C. Clip **120** includes a strip portion **122**, two first attachment arms **124** and a second attachment arm **126** as discussed above for FIGS. 6A-C. Clip **120** differs from clip **90** discussed above, by including a curved cable clamp **130** extending from an end **132** of a strip portion **122** that is opposite the first and second attachment arms **124** and **126**. The cable clamp **130** is particularly useful for holding electrical connectors, such as a cable **26** of the safety switch **22** shown in FIG. 2. The clip **120** can also be used in a same or similar manner to the clip **70** discussed above, such as securing the cable **26** to a vehicle door. The clip **120** could include the optional countersunk mounting apertures, if a single, dual-purpose clip is desired. As will be appreciated by those skilled in the art following the teachings herein provided, various and alternative sizes, shapes and configurations are available for the clips **90** and **120** as seen. For example, the cable clamp can optionally extend from the end of the second attachment arm (as illustrated in phantom in FIG. 7C) that is opposite the strip portion, thereby providing a planar surface on one side of the clip **120** for use in tight spaces.

The example clips provided are particularly useful in a method of retrofitting a vehicle door to include sensors such as the safety switch discussed herein. Each clip is selected for and applied to a particular location of the door. The first attachment arm of each clip is placed over a door flange of the vehicle door and the clip is pressed into a position where the second leg end of the barb leg is adjacent the door flange, such

6

as shown in FIGS. 4C and 6C. The safety switch is secured to the clip, optionally by attaching the intermediate mounting bracket, either before or after the clip is attached to the vehicle.

In one embodiment, the sensor **24** of the safety switch **22** may be connected to the clip by a mounting bracket, such as mounting bracket **32** discussed above. FIG. 8 illustrates an example embodiment in which a mounting bracket **32** is fastened to a clip. In FIG. 8, clip **40** is used for illustration, but it will be appreciated that any other example clip as seen herein can be used in a same or similar manner.

Fasteners **134** (e.g., rivets, screw, bolts, etc.) extend through the countersunk apertures **44** to connect the clip **40** to an optional spacer bracket **140**. The spacer bracket **140** is similarly connected by fasteners (e.g., rivets, screw, bolts, etc.) to the mounting bracket **32**. Attaching the mounting bracket **32** to the clip **40** before applying the clip to the door can desirably facilitate connection of the bracket **32** to the clip **40**. The bracket **32**, which will likely include more than one clip **40**, can be easily attached by clipping the attached clips over a door flange in the manner discussed above.

FIGS. 9-11 illustrate the sensor switch applied to a vehicle door. FIGS. 9 and 10 illustrate the attachment of the clip and mounting bracket combination of FIG. 8 to an "L"-shaped flange **145** of a vehicle door **150**. As discussed above, the flange is formed of a first portion **146** welded to a second portion **148**. In the embodiment of the clip **40** shown, the barb legs **60** are designed to contact the bottom surface of the first portion **146** of the flange **145**. As mentioned above, by having the barb legs **60** contact the first portion **146**, the clip **40** is assured a secured fit even when the flange components **146** and **148** are slightly misaligned. In FIGS. 9 and 10, a sensor **24** is shown mounted in the mounting bracket **32**.

FIG. 11 illustrates the clip **90** attached to an "I"-shaped flange **165** of a door **160**. The clip **90** is attached to a spacer bracket **162**, which allows for attachment of the mounting bracket **32** at a ninety degree angle to the flange **165**. In this embodiment, one type of mounting bracket can be used for both "I"-shaped and "L"-shaped flanges. As will be appreciated by those skilled in the art following the teachings herein provided, the mounting bracket **32** can be designed to attach directly to the clip or the mounting bracket can otherwise be configured to make the use of the spacer bracket **162** unnecessary.

Thus a clip and a mountable safety sensor strip are provided for retrofitting, for example, an up-armored military vehicle having a motorized door assist system. The clips, as seen, are easily mounted to portions of the door or vehicle frame during sensor installation.

The invention illustratively disclosed herein suitably may be practiced in the absence of any element, part, step, component, or ingredient which is not specifically disclosed herein. While in the foregoing detailed description this invention has been described in relation to certain preferred embodiments thereof, and many details have been set forth for purposes of illustration, it will be apparent to those skilled in the art that the invention is susceptible to additional embodiments and that certain of the details described herein can be varied considerably without departing from the basic principles of the invention.

What is claimed is:

1. An obstruction detection system, comprising: a safety switch including a plurality of sensors, each of the plurality of sensors comprising a sensing element molded in a casing and separated from an adjacent sensor by one of a plurality of electrical connectors; and

7

- a clip formed of a solid material including a strip portion, a first attachment arm extending at an angle from the strip portion, a second attachment arm extending from the strip portion, and a at least two barb legs, the at least two barb legs disposed at an angle relative to the strip portion and each of the at least two barb legs having a first leg end and a second leg end opposite the first leg end, the first leg end of each barb leg connected to the second attachment arm and the second leg end of each barb leg is disposed toward and spaced apart from the strip portion.
2. The system according to claim 1, wherein each of the plurality of sensors comprises a touch-sensitive sensor and the casing comprises a deformable polymer material.
3. The system according to claim 1, wherein the plurality of electrical connectors comprise a plurality of cables enclosed by a polymer casing.
4. The system according to claim 1, further comprising a mounting bracket.
5. The system according to claim 4, wherein the mounting bracket is secured to the strip portion of the clip for attaching to one of the plurality of sensors.
6. An obstruction detection system, comprising:
a safety switch including a plurality of sensors, each of the plurality of sensors comprising a sensing element

8

- molded in a casing and separated from an adjacent sensor by one of a plurality of electrical connectors;
- a clip including a strip portion, a first attachment arm extending from the strip portion, and a barb leg disposed at an angle relative to the strip portion and including a first leg end and a second leg end opposite the first leg end, the barb leg connected at the first leg end to the second attachment arm and the second leg end is disposed toward and spaced apart from the strip portion; and
- a second clip, the second clip including: a strip portion; a first attachment arm extending at an angle from the strip portion; a second attachment arm extending from the strip portion; a cable clamp extending from an end of the second attachment arm opposite the strip portion or an end of the strip portion opposite the first attachment arm; and a barb leg disposed at an angle relative the strip portion and including a first leg end and a second leg end opposite the first leg end, the barb leg connected at the first leg end to the second attachment arm and the second leg end is disposed toward and spaced apart from the strip portion.

* * * * *