



Battery Chargers Comparison

Charger		U/L	RoHS	Power Out	Input Voltage	Output Voltage	Battery Type
	CS1201A	1012		65A	90 - 150 VAC	24 VDC	SLA
	CS1201B	60601-1		65A	90 - 150 VAC	24 VDC	SLA
	CS1202	--		65A	90 - 240 VAC	24 VDC	SLA
	CS1202B	60601-1		65A	90 - 240 VAC	24 VDC	SLA
	CS1204	1012		120A	90 - 240 VAC	24 VDC	SLA
	CS1204L	1012		120A	90 - 240 VAC	24 VDC	SLA
	CS1204B	1012		120A	90 - 240 VAC	24 VDC	SLA
	CS1207C	--		45A	19 - 33 VDC	16 - 30 VDC	NiMH/NiCd
	CS1207D	--	Y	45A	19 - 33 VDC	16 - 30 VDC	NiMH/NiCd
	CS1232	60601-1	Y	110A	90 - 240 VAC	24 VDC	SLA

Specifications subject to change without notice.



Visit our website: www.controls.com
by scanning this QR code with your
smart phone.



BR0083-00



CONTROL SOLUTIONS LLC™
2520 Diehl Road, Aurora, Illinois 60502
Tel: 630.806.7062 Fax: 630.806.7065
www.controls.com